

PORCELANATO ESMALTADO / GLAZED PORCELAIN

60X60 PORCELANATO PULIDO TORENTO

GRUPO / GROUP Bla 60X60 RECTIFICADO

MORE SALES

NORMA / NORM ISO 13006

ENSAYO / STANDART

REQUERIMIENTO / SPECIFICATIONS

TECHNICAL FEATURES			UNITS	SPECIFICATIONS	STANDARD	
1. Dimensions and surface quality	1.1	Length	mm	600.0 ± 0.3% (or Max ± 0.6)	ISO 10545 -2	
	1.2	Width		600.0 ± 0.3% (or Max ± 0.6)		
	1.3	Thickness		8.0 ± 2%		
	1.4	Straightness of sides		600.0 ± 0.3% (or Max ± 0.6)		
	1.5	Rectangularity		848.5 ± 0.3% (or Max ± 0.8)		
	1.6	Surface flatness		1.6.1 Centre curvature (vs diagonal)		848.5 ± 0.4% (or Max ± 1.0)
				1.6.2 Edge curvature		600.0 ± 0.4% (or Max ± 0.8)
1.6.3 Warpage (vs diagonal)			848.5 ± 0.4% (or Max ± 1.0)			
1.7	Surface quality	-	A minimum of 95 % of the tiles are to be free from visible defects which can impair the appearance of a major area of tiles			
2. Physical properties	2.1	Water absorption	%	≤ 0.5%, Individual maximum 0.6 %	ISO-10545-3	
	2.2	Modulus of Rupture	N/mm ²	Average Minimum 35 Individual minimum 32	ISO-10545-4	
	2.3	Breaking strength	N	≥ 1,300	ISO-10545-11	
	2.4	Resistance to superficial abrasion	-	PEI 2	ISO-10545-7	
	2.5	Thermal shock resistance	—	Resists	ISO-10545-9	
	2.6	Frost resistance	—	Resists	ISO-10545-12	
	2.7	Dynamic coefficient of friction (DCOF)	2.7.1 Dry	—	≤ 0.42	ANSI A326.3
2.7.2 Wet			—	≤ 0.42		
3. Chemical properties	3.1	Resistance to household chemicals and swimming pool salts	—	Mínimum GB	ISO-10545-13	
	3.2	Resistance to staining	—	Mínimum Class 3	ISO-10545-14	

REFERENCIA / REFERENCE

A, ES. Producto fabricado para Cerámica San Lorenzo SAC, según requisitos de la Norma INTERNACIONAL ISO 13006: "Dry -Pressed Ceramic Tiles", Annex G (Normative), Table G.1- Requirements for dry -pressed ceramic tiles-Group Bla, Ev ≤ 0.5%.Las dimensiones, el tono y peso de las piezas presentan variaciones normales por el proceso de cocción. **A, EN.** Product manufactured for Cerámica San Lorenzo SAC, according to the requirements of the INTERNATIONAL Standard ISO 13006: "Dry -Pressed Ceramic Tiles", Annex G (Normative), Table G.1- Requirements for dry -pressed ceramic tiles-Group Bla, Ev ≤ 0.5 %.The dimensions, tone and weight of the pieces present normal variations due to the firing process.

B, ES. Evite que el material cerámico tenga contacto con productos químicos tales como Ácido Muriático, Ácido Fluorhídrico, Cloro, Gasolina, Thiner, Diésel, Limpiadores que contengan Hidróxido de Potasio y otros similares, dado que el uso de dichas sustancias, puede provocar cambios severos en la superficie de las losetas, alterando su apariencia original. **B, EN.** Prevent the ceramic material from coming into contact with chemicals such as Muriatic Acid, Hydrofluoric Acid, Chlorine, Gasoline, Thiner, Diesel, Cleaners containing Potassium Hydroxide and other similar products, since the use of such substances can cause severe changes in the surface of the tiles, altering their original appearance.

PRODUCTO / PRODUCT

Imagen Referencial / Referential Design



ES. Este producto tiene 3 caras.
EN. This product has 3 faces.


CARACTERÍSTICAS / CHARACTERISTICS

Cuerpo / Body	Uso / Use	Tipología / Typology	Acabado
Porcelanato / Porcelain	Piso / Floor	Marmoleado	Pulido
Superficie / Surface	Color / Color	Tránsito / Transit	Antideslizante / Anti-slip
Liso / Smooth	Ceniza / Gris	Bajo / Low	No

EMBALAJE / PACKING

Información para una Caja / Single box information	Información para un Pallet / Single pallet information		
Piezas / Pieces	m2	Cajas / Boxes	Kg
4	1,44	44	1,100,00

GRADO DE DESTONALIZACIÓN / DEGREE OF DETONALIZATION



5. Aceptación del Proveedor / Acceptance of Supplier

ES. Reconocimiento y aceptación de los términos y requisitos definidos o referenciados en esta Especificación Técnica. **EN.** Acknowledgment and acceptance of the terms and requirements defined or referenced in this Technical Specification.

Compañía / Company

Nombre / Name	MORE SALES INTERNATIONAL LLC	Título / Title	DIRECTOR
Firma / Signature	ALVARO DA SILVA	Fecha /	28 - 10 - 2024
Sello / Seal			

NOTA, ES. Cualquier incumplimiento de las especificaciones contenidas en este documento está sujeto a reclamación, siendo totalmente responsabilidad del proveedor, la reposición parcial o total del producto y todos aquellos gastos incurridos como consecuencia de incumplimientos técnicos detectados durante la recepción del mismo, para ser comercializado, y/o en el proceso de instalación. **NOTE, EN.** Any noncompliance with the specifications contained in this document is subject to claim, totally being under the responsibility of the supplier, the partial or total replacement of the product and all those expenses incurred as a result of technical noncompliances detected during reception thereof, to be marketed and / or in the installation process.